


Polymer Modified Asphalt Membrane

Self Adhesive Underlayment




Description: ALCO Shield[™] SMOOTH self-bonding membrane that is waterproof and has self-sealing properties. Excellent application for mechanically fastened wood panel subfloors under hard wood floors.

ALCO Shield SMOOTH is a polymer modified asphalt membrane, fiberglass reinforced, with a smooth, skid resistant surface for installation.

Specifications:

ASTM D-1970

MEETS: Miami-Dade County Approval and Florida Building Code



ALCO Shield SMOOTH texture shown.

Physical Properties:

Membrane Thickness: Approximately 50 mils
 Application Method: Self Adhering
 Surface Composition: Smooth Film Surface
 Membrane Reinforcement: Fiberglass Mat
 Backing Material: Split Silicone Coated Release Film

Roll Size: 195 Sq. Ft.
 Roll Weight: 47 Lbs
 Roll Width: 36"
 Roll Length: 65.0 Feet

Test Results

Underlayment Product	ASTM 1970	ASTM D-228	ASTM D-903	ASTM D-4073	ASTM 96 RAS
ALCO Shield SMOOTH	Pass	Pass	Pass	Pass	Pass



We warrant our materials to be of good quality and will replace materials found defective, providing, however, that the buyer shall examine the materials when received and promptly notify us of any defects before the materials are used or incorporated into a structure for which they are intended. *Visit our Website for full Warranty.*

